

AMENDMENTS TO THE CLAIMS

1. (Previously Presented) A method of distributing data across a network, the method comprising:
 - providing a distribution device configured to distribute packets of data across a set of equal-cost paths in the network;
 - determining if a set of equal-cost paths exist; and
 - distributing the packets across the paths based on at least one attribute of each of the packets,
 - wherein the distributing comprises using a pointer portion from a first set of instructions of a first compilation set of instructions to select a second set of instructions from a second compilation set of instructions, and
 - wherein the first set of instructions includes a first value that specifies how much weight is to be given to each equal-cost path in the set of equal-cost paths.
2. (Previously Presented) The method of claim 1, wherein the distributing comprises distributing the packets based on source addresses.
3. (Previously Presented) The method of claim 1, wherein the distributing comprises distributing the packets based on next-hop addresses.
4. (Previously Presented) The method of claim 1, wherein the distributing comprises performing a hashing function on the attribute.
5. (Currently Amended) A method of distributing data across a network, the method comprising:
 - providing a distribution device configured to distribute a set of packets of data across a set of equal-cost paths in the network; and
 - distributing each packet in the set of packets across the set of equal-cost paths according to a weighted distribution so that at least one of said packets is given greater

weight to be distributed across at least one of said equal-cost paths than at least one other of said equal-cost paths, said packet weight corresponding to a number of entries stored in a memory, wherein the distributing comprises

obtaining a match between a longest prefix in a first packet and a portion of a first set of instructions in a first compilation of sets of instructions, and

using a pointer portion from the first set of instructions to select a second set of instructions from a second compilation of sets of instructions, wherein the first set of instructions includes a first value that specifies how much weight is to be given to each equal-cost path in the set of equal-cost paths.

6. (Previously Presented) The method of claim 5, wherein the distributing further comprises using a packet attribute from each packet to perform the weighted distribution.

7. (Previously Presented) The method of claim 6, wherein the distributing comprises performing a hashing function on the packet attribute.

8 (Cancelled)

9 (Cancelled)

10. (Currently Amended) The method of claim [[9,]] 5, wherein the distributing comprises:

performing a hashing function on an attribute of the first packet to obtain a hashed result;

dividing the hashed result by the first value, thereby obtaining a remainder value, and using the remainder value to obtain an offset;

adding the offset to the first pointer to select the second set of instructions,

wherein the second set of instructions includes a pointer to a third set of instructions in a third compilation of sets of instructions.

11. (Previously Presented) The method of claim 10, wherein the distributing further comprises forwarding the first packet to a port designated in the third set of instructions.

12. (Original) The method of claim 5, further comprising updating a compilation of sets of instructions used to perform the weighted distribution, wherein the compilation is updated based on a best-fit algorithm.

13. (Original) A distribution device, the device comprising:
a set of ports; and
a first distribution unit, including a device logic, wherein the first distribution unit is configured to use the device logic to distribute a packet of data entering the device through a first port among the set of ports to a second port among the set of ports, the device logic comprising:

a first lookup unit including an acknowledgement unit for acknowledging whether multiple equal-cost paths exist, a first referencing unit for referencing a second lookup unit when multiple equal-cost paths do exist, and a second referencing unit for referencing a third lookup unit otherwise,

the second lookup unit including a second distribution unit for distributing the packet across the set of ports and a third referencing unit for referencing the third lookup unit, and

the third lookup unit including a selection unit for selecting the second port.

14. (Original) The device of claim 13, wherein, in the second lookup unit, multiple entries, each referencing a common set of instructions in the third lookup unit, are included.

15. (Original) The device of claim 14, wherein, in the second lookup unit, a different number of entries resulting in the packet being distributed to the first path than to a second path are included.

16. (Cancelled)

17. (Cancelled)